



FUEL TYPE: **ELECTRICITY**





We can give you a solar heating performance estimate for your town, city or very close by. This includes most countries in the world. The following chart shows the SIS Solar Air Heater performance and savings for cities in the United States and Canada. If your city is not represented pick a city at the same latitude as yours or send us an email and we will send you back the results.

Email: info@solarinfrasystems.com

Please Put in Subject line: What are my Solar Savings?

Please provide in email:

- Your email address
- Your full home address (house number, street, city, (province, state, region) and country)
- The main fuel type that you use
- What it is costing you annually (Canadian or American dollars please)
 Briefly describe the window or area you plan on putting the solar air heater (unobstructed, southern facing, no overhanging roof)

For most international regions we use a Government of Canada/NRC CanmetENERGY developed program and NASA solar data to show the annual fuel savings for just those months which would require a heater. (www.retscreen.net)

* NOTE: Follow installation instructions for optimum results

Heater Installation

The SIS Solar Air Heater has been developed to easily install in a room and operate like an electric room heater. In an average installation, the solar air heater is equivalent to about a 300 to 500 watt electric space heater, depending on the area you live in. The solar heater fan circulates the room air through the staged solar collectors in the heater that heat the air flow with solar energy. The solar heater fan operates by the sunlight shining on a photovoltaic panel (PV) so, unlike a room electric space heater, there is no household electric power required. The solar air heater hangs or is placed in a south facing window and uses solar radiation to heat the room air, to make up the room heat lost through the walls, ceiling, windows, and doors.

Window / Location

Make sure you have a south facing window that will take a solar air heater approximately 24 inches x 48 inches. The heater will fit between the glass and blind or curtains . There is room for venetian blinds which should be left slightly open to allow air flow through the blind louvers. Do not let the front of the heater touch the glass as it will cause a reduction in heat. If the outside temperature is zero $(0^{\circ}F / -17^{\circ}C)$, the inside glass of a standard double pane window will only be about $44^{\circ}F$ ($7^{\circ}C$). You are also losing appoximately 34 btu/hr per sq.ft. area of the window, through conduction and radiative heat loss.

Remember, if the window is low-E glass and/or argon filled, the solar radiation entering the window is filtered too low to make the solar air heater run effectively.

Shading

Look out the window and see if there is shading that will block the sun. In winter the sun is low in the sky and houses or trees can block the solar energy. If you have high trees on the east and west sides of the house, these will cut off your winter morning and afternoon solar radiation (even trees that lose their leaves.) Roof overhangs and depth of the window may also cut off 2-3 hours of solar radiation in the mornings and afternoons. This can cause a reduction in the effectiveness of the solar air heater.

Solar Air Heater Performance Table

The following table calculates how a solar air heater will perform in a room, with a double pane window, at a room temperature of 70°F (21°C), in a city at a specific latitude. (Important for the winter sun orientation.) If your state/province or location is not listed, pick a site closest on the same latitude as where you live. (NOTE: We are constantly adding locations. If your location is not listed, let us know.) The annual average temperature and heating months are listed for each major city. The annual heating months are used to calculate the fuel used to keep the room at the set temperature. The heating zone map will give you an idea of heating costs throughout the country. The solar air heater also uses the annual heating months, but since the sun does not shine all the time in most cities, it also factors the amount of sunny days during these heating months. Winter (65-70%) Spring and Fall (70-80%) Summer (not calculated if it is not a heating month) (80-90%).

Fuel Table Calculation

The fuel table shows the latest unit price for the city and the total fuel cost to heat the room for the annual heating months. The annual fuel cost is also shown for the solar air heater that uses free solar energy and the cost of the home fuel to make up for the non-sunny days during the heating months. The difference between the normal heating fuel used with no solar and the heating fuel used with a solar air heater is the annual solar savings for the heating months.

A simple payback is calculated by dividing the manufacturer's suggested retail price with the annual cost with solar, to show the number of years it will take to pay for the cost of the solar heater, in fuel savings.

The 15 year fuel savings give you an idea of what a solar air heater can save, where energy is increasing 10% per year, inflation is 2% and a discount of 5%. (Take a look on the Electricity Table at the variation in electricity costs per kwh that is happening all over the country.)

	Fuel: I	Electri	citv															
SIS Air Heater				MFGS Re	tail Price	\$ 475												
Room Size:						•	ner 2014 St	ate/p	rovino	e A	verage.							
Heater Air Flow:					(b) 15 year calculation includes10% fuel increase po													
Window:	Std double pane glass				(c) Simply payback:: number of			of years to recover cos				t of heater based			ed on a	annual fue	sav	ings
Solar energy reduction 30%						000/					_			= 001	- (0400			
Data Calculations:					5 , Low E glass reduce 60% RGY program with NASA solar data (www.retscr					Room Tempera			rature	/0°I	F (21°C)		
ELECTRICITY Site Solar D			-	SIS Solar Heater				Solar Savings with Residentia					l Fla	ctrical l	-leating			
ELECTRIC		<u> </u>	to oolal bi	Double		Annual	I Houter		Total Danings		1103	lacilla	Net		louting			
		Ave	Ave	Pane	Heating	SIS Solar	SIS Solar	Fue	l Unit	_	nnual	Ar	nual		nnual	Simple		5 year Fuel
City	Latitude	annual	Heating	Window	Zone	Heater Delivered	Heater		t/kwh	ı	el Cost		l Cost		uel	Payback		avings
		temp °F	Months	Solar Radiation	(See Map)	Million	Ave Temp. Rise °F	\$	(a)	no :	Solar \$	Witi	Solar		vings n Solar	Years (c)		h Solar
				kwh/ft2/D		BTU						\$ (c)		(- /	\$(b)			
AK Anchorage	N61.2°	37.4	12	0.156	6	3.4	11.8	\$	0.21	\$	1,073	\$	560	\$	513	0.93	\$	17,467
CA Los Angeles	N33.9°	62.5	7	0.322	2	2.7	14.9	\$	0.18	\$	201	-\$	70	\$	271	1.75	\$	8,974
CO Denver	N39.8°	50.3	9	0.299	5	3.5	15.3	\$	0.13	\$	459	\$	124	\$	335	1.42	\$	11,229
FL Maimi	N25.7	75.1	0	0.306	1	1.8	13.1	\$	0.12	\$	26	-\$	56	\$	82	5.79	\$	2,393
GA Atlanta	N33.4°	60.2	7	0.284	2	2.3	12.6	\$	0.13	\$	267	\$	47	\$	220	2.16	\$	7,197
HI Honululu	N21°	77	0	0.351	1	2.2	13.9	\$	0.38	\$	23	-\$	328	\$	351	1.35	\$	11,816
ID Boise	N43.6°	51.9	9	0.288	4	2.6	11.5	\$	0.11	\$	263	\$	107	\$	156	3.04	\$	4,987
IL Chicago	N42°	50.2	8	0.257	5	2.4	12.3	\$	0.12	\$	419	\$	161	\$	258	1.84	\$	8,542
KA Witchita	N37.7°	56.8	7	0.296	3	2.3	13	\$	0.13	\$	310	\$	138	\$	172	2.76	\$	5,519
MA Boston	N41.7°	50.6	10	0.237	4	2.7	11.1	\$	0.16	\$	542	\$	194	\$	348	1.36	\$	11,708
MN Minneapolis	N44.9°	46.5	9	0.254	5	2.9	13.2	\$	0.13		557	\$	212	\$	345	1.38	\$	11,568
MO St. Louis	N38.7°	55.9	7	0.263	3	1.8	10.1	\$	0.12	<u> </u>	285	-	152	\$	133	3.57	\$	4,187
MT Butte	N46.0°	40	12	0.249	5	3.7	12.5	\$	0.11	<u> </u>	585	-	217	\$	368	1.29	\$	12,392
NM Albuquerque	N35°	57.2	7	0.362	4	3	16.6	\$	0.14		257	\$	47	\$	210	2.26	\$	6,892
NV Los Vegas	N36.1°	68.6	5 8	0.368	3	4.1	17.6	\$	0.13	<u> </u>	180	-	78	\$	258 371	1.84	\$	8,548
NY New York OR Portland	N40.8° N45.6°	54 54	10	0.257	3	2.3	11.6 11.8	\$	0.20	\$	571 310	-	200 77	\$	233	1.28 2.04	\$	12,490 7,670
TX Dallas	N36.0°	55.3	7	0.322	1	2.8	15.2	\$	0.11	<u> </u>	339	\$	81	\$	258	1.84	\$	8.534
VT Burlington	N44.5°	46.3	9	0.243	5	2.7	12.2	\$	0.18	l i	753	•	296		457	1.04	\$	15,482
WA Seattle	N47.5°	52.1	10	0.217	4	2.8	11.4	\$	0.09		274		83		191	2.49	\$	6,194
WI Madison	N43.1°	47.3	9	0.255	5	2.9	13	\$	0.15	 	629		225	\$	404	1.18	\$	13,633
AB Edmonton	N53.3°	35.9 (2.16°C)	12	0.232	5	3.5	13.2	\$	0.15	\$	886	\$	358	\$	528	0.90	\$	17,981
BC Vancouver	N49.0°	49.4 (9.66°C)	12	0.202	5	2.6	9.6	\$	0.11	\$	385	\$	133	\$	252	1.88	\$	8,336
ONT Toronto	N43.7°	45 ((7.22°C)	10	0.233	5	2.5	11.2	\$	0.17	\$	756	\$	314	\$	442	1.07	\$	14,944

Table: SIS Solar Air Heater Perfomance for Cities in the United States and Canada

Technology and products covered under patents USA 8,863,741, Sept 22,2014, Canada 2,736,792 Jan 22, 2013 and world patents pending.

Contact us to learn more about our revolutionary infrared technology.

Solar-Infra Systems International Ltd.

209-19138 26th Ave Surrey, British Columbia Canada V3S 3V7

Tel: 604 535 2056

Toll free (Canada & USA): 1-855-535-2056

